

NEC 2x2 LCD TileMatrix™ Video Wall Solutions

*Professional-Grade Display Bundle with Pull-out
Mounting System*

NEC Display Solutions' complete 2x2 LCD TileMatrix Video Wall Solutions provide an all-in-one, easy-to-configure solution that is ideal for dynamic digital signage, information display and command & control applications.

Exclusive TileMatrix and TileComp™ technologies, combined with the ultra-narrow bezel design of the 46" NEC X462UN, X462UNV, X463UN and 55" X551UN and the full adjustment capabilities of the Peerless-AV DS-VW765-LAND mount, provide for a near seamless video wall that is easy to configure, install and maintain. The ultra-narrow bezel of these X Series models offer down to 5.7mm between consecutive displays and built-in EdgeComp Technology that aids in brightness uniformity from center to edge of each display panel. With LED backlighting, a full high-definition panel and commercial brightness, the X463UN-TMX4P and X551UN-TMX4P deliver stunning imagery while minimizing power consumption. These bundles also have full HD panels with brightnesses up to 700 cd/m² and contain integrated temperature sensors and cooling fans that allow for 24/7 runtimes. When compared to 82"-108" single-screen displays, NEC's video wall solutions deliver a more cost-effective and easier-to-transport and install alternative for your application.



Highlights

- **Bundled solution** with everything required for a 2x2 video wall makes configuration and installation easy
- **Direct LED backlighting** improves power consumption and uniformity (X462UNV, X463UN and X551UN bundles only)
- **NEC Display Wall Calibrator Kit** features software and a sensor, allowing for accurate brightness intensity and white point matching from screen-to-screen for greater overall color uniformity
- **Peerless-AV pull-out mount** allows for full service capabilities and 6-axis adjustment for perfect alignment
- **TileMatrix technology** is integrated into each NEC display within the bundle, allowing for easy manipulation of a single picture to 2x2 format
- **TileComp** works in tandem with TileMatrix to compensate for the bezel width and create a more seamless video wall
- **Copy function** allows the user to apply the settings from one display to all others in the RS-232 daisy chain, reducing setup time and saving money (null modem cables included)
- **Thin-bezel design** provides for some of the smallest bezel widths in the industry
- **Industry's most extensive display control**, including RS-232, Ethernet connectivity, NaViSet Administrator 2 software and DDC/CI standard
- **24/7 runtimes** due to professional grade panels and integrated heat dissipation technologies
- **Fan-based technology** connected to internal heat sensors automatically turns on when temperatures reach certain thresholds. Designed to work in both portrait and landscape orientations, these fans can be always on or controlled remotely.
- **Overframe Bezel Kit** completes your solution by offering a "finished & framed" look (two kits included)
- **Remote Control and Ambient Light Sensor Kit** provides the entire video wall with one sensor that detects ambient light and delivers simple remote control functionality
- **Tripp Lite surge suppressor** features six outlets and prevents crashes, reboots and performance problems

NEC 2x2 LCD TileMatrix Video Wall Solutions

MODEL	X462UN-TMX4P	X462UNV-TMX4P	X463UN-TMX4P	X551UN-TMX4P
LCD MODULE				
Viewable Image Size	46"			55"
Native Resolution	1366 x 768	1920 x 1080		
Brightness (Typical/Max)	500 / 700 cd/m ²	320 / 450 cd/m ²	500 / 700 cd/m ²	
Contrast Ratio (Typical)	3000:1	3500:1	3000:1	3500:1
CONNECTIVITY				
Digital In	DisplayPort, HDMI, DVI-D			
Analog In	VGA 15-pin D-sub, 5BNC (RGBHV, DVD/HD or Video), BNC Composite, S-Video, RCA Composite**, RCA Component (Y, Cb/Pb, Cr/Pr)**			
Audio In	RCA Audio, Stereo Mini-Jack (2), HDMI Audio, DisplayPort Audio**			
External Control In	RS-232C, LAN, IR Remote, DDC/CI			
Digital Out	n/a	DisplayPort, DVI-D		
Analog Out	BNC Composite, 5 BNC (RGBHV, DVD/HD or Video)**			
Audio Out	RCA Audio	Stereo Mini-Jack, External Speaker Jack (2)		
External Control Out	RS-232, IR Remote			
Net Weight (without stand)	64.6 lbs. / 29.3 kg	53.6 lbs. / 24.3 kg	53.6 lbs. / 24.3 kg	77 lbs. / 35 kg

* Not applicable in all countries. Terms and conditions apply. Contact an NEC representative for more details.

** X462UN only

NEC X Series Components Included Cables

Qty. 1

DVI-D Male to DVI-D Male 5m cable used for connecting video source to first display



Qty. 4

DVI-D Male to DVI-D Male 3m cable used for daisy chaining digital video signal through video wall (X462UN-TMX4P includes SB-L008WU)



Qty. 3

D-Sub 9-pin Female to D-Sub 9-pin Female 10-ft. null modem cable used for daisy chaining control signals through the video wall



Product warranty, if any, is provided directly by the manufacturer of the product. Warranty periods and warranty terms and conditions are as specified by each manufacturer in their applicable warranty statement. NEC does not provide any warranty on third party (non-NEC manufactured) products.

Shared Components

Tripp Lite surge suppressor - Qty. 2

- Features six outlets/6-ft. cord
- \$50,000 Ultimate Lifetime Insurance (US/CDN)
- Network grade surge suppression rated at 2350 joules/97,000 amps
- Prevents system crashes, reboots and performance issues
- Keyhole mounting tabs allow permanent installation
- Lighted power switch confirms power on/off status
- Widely spaced outlets accommodate up to four large transformer plugs without blocking outlets

Peerless Pull-Out Mount

Qty. 4

Peerless-AV full-service video mount (DS-VW765-LAND) features customizable wall spacers for perfect placement and a pull-out/prop-open mechanism for quick service access.



KT-LFD-CC - Qty. 1

- Display Wall Calibration Kit includes the calibration software on a USB drive and a color sensor, a version of the DataColor Spyder 4 Series

KT-RC - Qty. 1

- Remote Control and Ambient Light Sensor Kit maximizes brightness efficiency and power usage for video wall products.

Accessories

KT-46UN-OF - Qty. 2

- Overframe Bezel Kit creates a uniform look for X462UN video walls

KT-46UN-OF2 - Qty. 2

- Overframe Bezel Kit creates a uniform look for X463UN and X462UNV video walls

KT-55UN-OF - Qty. 2

- Overframe Bezel Kit creates a uniform look for X551UN video walls

NaViSet, TileComp and TileMatrix are trademarks of NEC Display Solutions. All other brand or product names are trademarks or registered trademarks of their respective holders. Product specifications subject to change.

©2013 NEC Display Solutions of America, Inc. All rights reserved. 25.NEC.80.GL.UN.102 rev. 10.31.13

NEC Display Solutions

500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE

necdisplay.com

NEC